



OVER SURFACE SPACING  
(CREEP DISTANCE) = 2.188"

**AVAILABLE THREADS**

**UNC THREAD STYLES**

PART NUMBER	INSERT SIZE	MATERIAL
4175-A3	5/16-18 X 3/8	ALUMINUM
4175-S3	5/16-18 X 3/8	STEEL
4175-A4	3/8-16 X 3/8	ALUMINUM
4175-S4	3/8-16 X 3/8	STEEL
4175-S5	3/8-16 X 9/16	STEEL

**METRIC THREAD STYLES**

4175-A3/M8	M8 X 1.25 X 9.5	ALUMINUM
4175-S3/M8	M8 X 1.25 X 9.5	STEEL
4175-A4/M10	M10 X 1.50 X 9.5	ALUMINUM
4175-S4/M10	M10 X 1.50 X 9.5	STEEL
4175-S5/M10	M10 X 1.50 X 14.2	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL  
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



**MAR-BAL, Incorporated**  
5400 Reserve Way  
Dublin, VA 24084  
www.mar-bal.com

TITLE <b>4000 SERIES OCTAGON INSULATOR</b>	
PART NUMBER: <b>4175-XX</b>	SUGGESTED INDOOR RATING: <b>2.0 kV</b>
SHEET 1 OF 1	SCALE 1.000